



ECOABSORB M

Ecological industrial absorbent medium granules for pollution spills

DESCRIPTION

It is an Industrial absorbent of special granulometry that improves the absorption, made in the Canary Islands from 100% recycled materials. It consists of a mixture of granules and powder that allows it to act in a faster and more effective way than other absorbents

APPLICATIONS

ECOABSORB M is an industrial absorbent, which has very high absorption capacity, suitable for the most difficult cases, regardless of the type of chemical agent or oil contaminated. The low volatility of the grain together with the excellent absorption power of the powder make it ideal both outdoors and indoors. Being a water-repellent product, it is able to absorb the spills produced in the presence of water without absorbing it, thus saving unnecessary waste.

It is perfect for oils or chemical agents discharged on hard and hard surfaces, whether highways, freeways or industrial enclosures. The industrial absorbent ECOABSORB M provides medium level surface and water cleaning. It also keeps waste disposal costs low. Suitable for use in:

- Naval and port sector
- Routes of traffic.
- Industrial and commercial establishments.
- Repair and manufacturing establishments.
- Transport and traffic companies.
- Trade in mineral oils, oil and transport
- Domestic activities and workshops, houses and garages.

PROPERTIES

- Easy and fast performance.
- Economic
- Application in oils and hydrocarbons.
- Great absorption capacity and no caking.
- Compatible with the work environment.
- Water resistant.
- Does not adhere to shoe soles, vehicle wheels, etc ...

HOW TO USE

For soil spills, cover the stain with ECOABSORB M, wait the time necessary for it to absorb and gently rub with a brush over the stain, and collect with a shovel.

For spills on water, cover the edge of the spill first to avoid spreading and penetrate through the distribution of ECOABSORB M, into the stain until completely covered, remove and collect the product with shovels, nets, etc ...

Use appropriate personal protective equipment.

Technical data

- Base material: 100% recycled
- Granulometry: 250µm -4mm,
- Densities range from 210-450 g / lt
- Does not contain VOCs. (Volatile organic compounds), we know that they are air pollutants and when mixed with nitrogen oxides, they react to form ozone.
- Does not expire, nor lose effectiveness over the years
- Classification of oil binding substances according to the German Federal Ministry of Environment are Type I, II, III, R.

Type I Oil binder with special suitability for use in all types of water

Type II Oil binder for quick use on small water surfaces and on dry land

Type III Oil binder for special needs on firm ground and traffic surfaces

Additive R Its use guarantees a sufficiently good grip of the roadway

Presentation

3 and 20lt bags

NOTE:

The information and technical data reflected here are indicative and are subject to change without notice. They are based on data and knowledge considered to be true and accurate. However we have no control over the conditions under which our products are transported, stored, handled or used by our customers. Therefore, our guarantee is limited exclusively to product quality. No information or recommendation construed to violate any rule or legal provision in force.